

# ROLINE Gigabit Industrial Switch, 5x RJ-45, 1x LC, managed

<b>Product No.</b>	21.13.1159
<b>Manufacturer</b>	ROLINE
<b>Manufacturer No.</b>	21.13.1159
<b>EAN (single piece)</b>	7611990199495



**A managed 6-port Gigabit Ethernet switch which is featured with five copper ports, one mini-GBIC (SFP) port and the following advantages in a small footprint box.**

- Provides 5 10/100/1000Base-T ports and 1x 1000Base-SX port
- Provides in-band web-based management interface
- All copper ports support auto-negotiation and auto-MDI/MDI-X detection
- Provides full wire speed forwarding
- Supports 802.3x flow control for full-duplex and backpressure for half-duplex
- Provides port status, statistic monitoring and control function
- Supports port-based and 802.1Q Tag-based VLAN
- Provides QoS function
- Provides 802.1x authentication
- Supports configuration backup and upload
- Provides port link aggregation (trunking) function
- Provides port mirroring function
- Industrial-rated emission and immunity performance
- Power: Input: 6,5 - 32V DC, Consumption: 3.6W (max.)
- Operating Temperature - 40 °C - +70 °C
- DC Input via terminal block or DC power jack (6.3mm/2.0mm)
- Dimensions: 144 X 104.5 X 26mm (WxDxH)
- As according Power Supply Unit we recommend 21.13.1311

## Technical specifications

Manufacturer	ROLINE
Product group	Network Switches
Product type	Gigabit Ethernet Switch
Colour	black
Scope of delivery	Switch, power supply, manual, 1x GBIC
Network standard	Gigabit Ethernet
LAN (Mbps)	10/100/1000
Quantity of ports	5
Gigabit Ethernet Ports RJ-45	5
Mounting form	DIN Rail
Stackable	No
Technical particularity	- 40 °C - +70 °C
Dimensions (HxWxD)	106 x 144 x 26 mm
Power supply unit (internal/external)	External
Operating temperature min.	-40 °C
Operating temperature max.	70 °C
Height	106 mm
Width	144 mm
Depth	26 mm
Weight	431.2 g